



## Dimensions, tolerances and weight of HP tubes

Inside diameter [mm]	Tolerance of inside diameter [mm]		D x t [mm]	Weight [kg/m]	Maximum length [mm]	
	H8	H9				
40	+0,039	+0,062	48 x 4	4,34	3 000	
			50 x 5	5,55		
			52 x 6	6,81		
			55 x 7,5	8,79		
50	+0,039	+0,062	60 x 5	6,78	4 000	
			62 x 6	8,29		
			65 x 7,5	10,64		
60	+0,046	+0,074	70 x 5	8,01	5 000	
63			72 x 6	9,77		
			75 x 7,5	12,48		
			73 x 5	8,38		
70			75 x 6	10,21		
			78 x 7,5	13,04		
	80	80 x 5	9,25	6 000		
		82 x 6	11,25			
85 x 7,5		14,33				
90 x 10		19,73				
90	+0,054	+0,087	90 x 5	10,48	6 000	
			92 x 6	12,73		
			95 x 7,5	16,18		
			100 x 10	22,20		
100			100 x 5	11,71		6 000
			102 x 6	14,21		
			105 x 7,5	18,03		
			110 x 10	24,66		
110			115 x 7,5	19,88		6 000
			120 x 10	27,13		
			125 x 7,5	21,73		
			130 x 10	29,59		

The diameters 80 x 10 mm (17,26 kg/m) and 126 x 8 mm (23,28 kg/m) upon agreement.