



Dimensions of oil tubes

Outside diameter			Wall thickness			Weight	
Size	[inch]	[mm]	Size	[inch]	[mm]	[lbs/ft]	[kg/m]
TUBING (plain end)							
1,05	1,05	26,7	1,14	0,113	2,87	1,13	1,70
		(26,67)	1,48	0,154	3,91	1,48	2,19
1,315	1,315	33,4	1,70	0,133	3,38	1,68	2,52
		(33,40)	2,19	0,179	4,55	2,17	3,21
1,660	1,660	42,2 (42,16)	-	0,125	3,18	2,05	3,05
			2,30	0,140	3,56	2,27	3,43
			3,03	0,191	4,85	3,00	4,51
1,900	1,900	48,3 (48,26)	-	0,125	3,18	2,37	3,55
			2,75	0,145	3,68	2,72	4,09
			3,65	0,200	5,08	3,63	5,41
2 3/8	2,375	60,3 (60,32)	4,00	0,167	4,24	3,94	5,83
			4,60	0,190	4,83	4,44	6,63
			5,80	0,254	6,45	5,75	8,56
2 7/8	2,875	73,0 (73,02)	6,40	0,217	5,51	6,17	9,15
			7,80	0,276	7,01	7,67	11,39
			8,60	0,308	7,82	8,45	12,57
3 1/2	3,500	88,9 (88,90)	7,70	0,216	5,49	7,58	11,31
			9,20	0,254	6,45	8,81	13,20
			10,20	0,289	7,34	9,92	14,76
4	4,000	101,6 (101,60)	9,50	0,226	5,74	9,12	13,56
			-	0,262	6,65	10,47	15,57
			13,20	0,330	8,38	12,95	19,27
4 1/2	4,500	114,3 (114,30)	12,60	0,271	6,88	12,25	18,22
			15,20	0,337	8,56	15,00	22,32
			17,00	0,380	9,65	16,77	24,90
CASING (without threading)							
4 1/2	4,500	114,3 (114,30)	9,50	0,205	5,21	9,41	14,01
			10,50	0,224	5,69	10,24	15,21
			11,60	0,250	6,35	11,36	16,90
			13,50	0,290	7,37	13,05	19,41
			15,10	0,337	8,56	15,00	22,29

Note: Tubes of OD 2.063 in (52,4 mm), 5 in (127 mm) and 5 1/2 in (139,7 mm) upon agreement. Dimensions in brackets are from edition API 5CT - 2005.